

CARMEL GROUP INC.

SAFETY DATA SHEET

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION				
Product Margin Wax Various Colors (Blue, Yellow, White & Red)			Revision date 10/23/17	
Previous revision date: 09/17/09	Product code MW40002 to MW40014 (See p.4)		Material use Dental Wax	
Manufacture's Name and issuing location CARMEL GROUP INC. 10220 ARMAND LAVERGNE AVE. MONTRÉAL, QUE. H1H 3N4 PHONE : 514-270-5377 FAX : 514-270-2025 INTERNET : www.carmelindustries.com			EMERGENCY PHONE NUMBER CANUTEC 613-996-6666	
SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS				
Hazardous Ingredients	CAS#	Amount	Exposure Limits	
			LD/50	LC/50
None as defined by OSHA 29 CRF 1910.1200				
SECTION 3 – HAZARD IDENTIFICATION				
Emergency Overview				
The product is not expected to present any unusual hazards in proper use (room temperature up to 104F/40C). Overheating is considered abnormal usage of the product.				
SKIN CONTACT	No danger at room temperature.			
EYE CONTACT	Not likely to occur because solid sheets at room temperature.			
INHALATION	No fume or aerosol at room temperature.			
INGESTION	This material is essentially inert and non-toxic. Regardless it should not be ingested.			
Potential Health Effects (NFPA Classification)				
Fire hazard : 1	Health Hazard : 0	Reactivity : 0	Personal Protection : See Section 8	
0 = Minimal 1 = Slight hazard 2= Moderate Hazard 3 = Serious Hazard 4 = Severe Hazard				
SECTION 4 – FIRST AID MEASURES				
EYE CONTACT	Exposure to fumes, vapors or smoke of the thermally degraded product can result in irritation to the eye and direct contact of the molten material will cause eye injury and burns. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Call a physician to attend to the injury.			
SKIN CONTACT	Exposure to fumes, vapors or smoke of thermally degraded product can result in irritation to skin and direct contact of the molten material will cause injury and burns. For burns apply running water over the injured area for 15 minutes. Do not attempt to remove any material bonded to skin. Call a physician to attend to the injury.			
INHALATION	Remove individual to a well-ventilated area for fresh air and call a physician to attend to the injury.			
INGESTION	Material is not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Call a physician.			
ADDITIONAL INFO				
SECTION 5 – FIRE FIGHTING MEASURES				
Extinguishing	Treat as an oil fire. For small fire use CO ₂ , dry powder or foam. For large fire use			

Media	Alcohol-type foam, universal-type foam or water fog.		
Special Firefighting Procedure	Use water spray cool fire-exposed containers and structures. Do not direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.		
Unusual Fire and Explosion Hazards	This product will burn if involved in a fire. This product will float upon water, so water spray is not suitable extinguishing agents as it may cause fire to spread.		
SECTION 6 – ACCIDENTAL RELEASE MEASURES			
Small Spills	Not likely to occur in solid state.		
Large Spills	Not likely to occur in solid state.		
SECTION 7 – HANDLING AND STORAGE			
Handling procedures	None special needed.		
Storage precautions	Normal precaution should be followed in handling and storage. Store in a dry place. Keep out of direct sunlight. Do not store at temperature : > 104F/40C		
SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION			
PERSONAL PROTECTION (ONLY IF MOLTEN)			
Respiratory protection	No special respiratory protection is normally required.		
Protective gloves	None are normally required.		
Eye protection	No special eye protection is normally required.		
Clothing	No special clothing recommended.		
SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Appearance Various Color Wax in Thin	Odor None	Physical state Solid @ 25°C / 77°F	Boiling point N / AV.
Melting point ~80°C/175°F	Specific gravity (H ₂ O=1) < 1	Vapor pressure (mm Hg) < 0.01 @ 25°C / 77°F	Solubility in water Insoluble
Solubility in organic solvent Soluble	Partitioning coefficient N / AV.	Flash point N / AV.	Percent volatiles Nil
SECTION 10 – STABILITY AND REACTIVITY DATA			
Stability Stable	Hazardous polymerization Will not occur.		
Incompatibility	Normally unreactive; however avoid contact with strong oxidizing agent (ex. Peroxides, chlorine), Sunlight or ultraviolet light, heat or high temperature.		
Hazardous decomposition products	Burning can produce noxious and toxic fumes, and the following combustion products: Oxides of carbon.		
SECTION 11 – TOXICOLOGICAL INFORMATION			
Carcinogenicity Not listed, not carcinogenic to date.	Mutagenicity / Teratogenicity Not listed		
Irritancy of Material N / Av.	Sensitizing Capability N / Av.		
Reproductive Effects None known	Synergistic Materials None known		
SECTION 12 – ECOLOGICAL INFORMATION			
This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant. Not expected to be acutely toxic to aquatic organism.			
SECTION 13 – DISPOSAL CONSIDERATION			
Incineration is probably the best mean of disposal. Dispose of in accordance with appropriate Federal, State and local regulation.			
SECTION 14 – TRANSPORT INFORMATION			

Dot Classification Not regulated if shipped at temperature under 100C / 212F or in containers less than 450 liter.	
IMDG Classification Not regulated if shipped at temperature under 100C / 212F or in containers less than 450 liter.	
UN / NA Hazard No. Not Applicable.	
ICAO Classification Not regulated if shipped at temperature under 100C / 212F.	
Other Forbidden by air at temperature over 100C / 212F.	
SECTION 15 – REGULATORY INFORMATION	
SARA Status	Section 311, 312 and 313 : None
TSCA Status	Ingredients listed in the TSCA inventory.
OSHA Status	None
WHMIS Status	Not a controlled material
CPR Compliance	Not Known
SECTION 16 – OTHER INFORMATION	
N/AV=NOT AVAILBLE	
SDS Originally made by Karl Pinard	Revised by Federico Segovia

The information contained in this document is derived from data supplied to Carmel Industries by the manufacturers or distributors of the raw materials combined to form this product. To the best of our knowledge all hazards have been noted for the intended use of the product and, since Carmel Industries cannot control conditions of use, the end user is obliged to determine the conditions permitting safe use of the product.

CARMEL GROUP INC.
MARGIN WAX PRODUCTS

Product code

MW40002
MW40003
MW40009
MW40014

Product Description Yellow

Margin Wax in 2 Oz Tin White
Margin Wax in 2 Oz Tin Red
Margin Wax in 2 Oz Tin Blue
Margin Wax in 2 Oz Tin